

TUBE.30

Magnetic drilling machine

 **EUROBOOR**

FOR PROFESSIONALS BY PROFESSIONALS


Technical data

	Metric	Imperial
Annular cutting	Ø 12 - 30 mm	Ø 1/2" - 1 3/16"
Twist drilling (Weldon)	Ø 1 - 13 mm	Ø 1/16" - 1/2"
Countersinking	Ø 10 - 35 mm	Ø 3/8" - 1 3/8"
<hr/>		
Length	275 mm	10 13/16"
Width	185 mm	7 1/4"
Height	326 - 416 mm	12 13/16" - 16 3/8"
<hr/>		
Stroke	90 mm	3 9/16"
Weight*	10.3 kg	22.7 lbs
Magnet (l x w x h)	187 x 165 x 83 mm	7 3/8" x 6 1/2" x 3 1/4"
Magnetic force	532 kg	1,175 lbs
Min. material thickness	3 mm	1/8"
Min. pipe diameter	76.2 mm	3"
Motor power	900 W	8.2 A
Total power	950 W	8.6 A
Speed		775 rpm
(no load)		
Speed		400 rpm
(load 900 W, 8.2 A)		
Spindle (Weldon)	19.05 mm	3/4"
Voltage		110 - 120 V / 60 Hz 220 - 240 V / 50-60 Hz

* Without power cord and handles



Round outer surface



Flat surface



Round inner surface



Euroboor makes every effort to meet quality and integrity requirements. That is why we as an organization are proud of the recognition of some leading organizations worldwide:



www.euroboor.com